

# Duct Liner Adhesive - HV

Qualifies for LEED Credit EQ 4.1

## Detail

Premium grade high viscosity duct liner adhesive.

- Water Based
- UL Classified
- Fast Dry Time
- Exceptional Coverage
- Water Resistant
- Cleans with soap and water or mineral spirits
- Excellent Tack
- Base: Synthetic Latex
- Color: Black
- Solvent: Water
- Weight per Gallon: 9.5 ± 0.5 lbs.
- Solids: 44 ± 2%
- Viscosity: 15,000 CP ± 1,000 CP
- Application Temp: 40°F to 90°F
- Storage Temp: 40°F to 90°F
- Dry Time: 10-20 minutes, depending on temperature, humidity, and application thickness
- Flammability: None
- Flash Point: No flash to boiling
- Coverage: Approximatley 500 sq.ft./gal., depending on application technique
- Freeze Thaw Stability: 5 cycles
- Shelf Life: (Unopened containers) 1 year
- Flame Spread: 0
- Smoke Developed: 0
- Meets ASTM C 916 Type II
- Meets NFPA 90A & 90B
- LEED v4 Compliant
- Contains antimicrobials and fungicides to prevent mold growth



## CONTACT

Office: 888.973.7600

1100 Ashwood Drive  
Suite 1102  
Canonsburg, PA 15317

[www.clward.com](http://www.clward.com)

## Packaging

Item	Description	Packaging	Weight
DLADHESIVEHV5	High Viscosity D L Adhesive - Black 5 gal pail	Each	46 lbs/pail
DLADHESIVEHV54	High Viscosity D L Adhesive - Black 54 gal drum	Each	555 lbs/drum
DLADHESIVEHV5W	High Viscosity D L Adhesive - White 5 gal pail	Each	46 lbs/pail
DLADHESIVEHV54W	High Viscosity D L Adhesive - White 54 gal drum	Each	555 lbs/drum