

# Lag Adhesive

Qualifies for LEED Credit EQ 4.1

## Detail

Lagging adhesive is used for bonding and sealing jackets of canvas, cloth or other fabrics and insulators to air conditioning ducts or cold water pipes.



- Water Based
- ASTM E-84 Certified
- LEED Compliant
- Low odor
- Non-flammable in wet state
- Fire retardant in dry state
- UV resistant
- Sag resistant
- Good dry time
- Base: Acrylic Latex
- Color: White or Black
- Weight/Gal: 11 lbs ±2%
- Viscosity: app. 75,000 cps
- Service Temp: -25°F to +175°F
- Application Temp: 40°F to +110°F
- Storage Temp: 40°F to +100°F
- Flammability: None
- Flash Point: No flash
- Dry Time: Touch 1 hour/Through 6 hours  
(depending on humidity, temperature, and thickness)
- Freeze Thaw: 5 cycles
- Coverage: 50 sq.ft. to 200 sq.ft.  
(depending on application rate)
- Bonding Time: 40 minutes
- Shelf Life: 2 years
- LEED Compliant



## Packaging

Item	Description	Packaging	Weight
LAGADHESIVE1B	Lagging Adhesive 1 gal Black	4 gallons/case	48 lbs/case
LAGADHESIVE1W	Lagging Adhesive 5 gal pail White	Each	64 lbs/pail
LAGADHESIVE5B	Lagging Adhesive 1 gal Black	4 gallons/case	48 lbs/case
LAGADHESIVE5W	Lagging Adhesive 5 gal pail White	Each	64 lbs/pail

## CONTACT

Office: 888.973.7600

1100 Ashwood Drive  
Suite 1102  
Canonsburg, PA 15317

[www.clward.com](http://www.clward.com)