


# Super Liner Sealer

Qualifies for LEED Credit EQ 4.1

## Detail

High viscosity water based fiberglass encapsulating coating specifically for spray applications.

- Water Based
- UL 723 Classified
- Fast Dry Time
- Contains EPA registered preservatives to prevent mold, fungus, yeast, mildew and yeast
- Exceptional Coverage
- Water Resistant
- Cleans with soap and water or mineral spirits
- Base: Synthetic Latex
- Color: Off white
- Solvent: Water
- Weight per Gallon: 10.75 ± 0.2%
- Solids: 54 ± 2%
- Viscosity: 15,000 CPS
- Application Temp: 45°F to 90°F
- Storage Temp: 40°F to 90°F
- Open Time: 10-20 minutes, depending on temperature, humidity, and application thickness
- Flammability: None
- Flash Point: No flash to boiling
- Coverage: Approximatley 200 sq.ft./gal., depending on application technique
- Freeze Thaw Stability: 5 cycles
- Shelf Life: (Unopened containers) 1 year
- Flame Spread: 0
- Smoke Developed: 0
- LEED Compliant



## CONTACT

Office: 888.973.7600

1100 Ashwood Drive  
Suite 1102  
Canonsburg, PA 15317

[www.clward.com](http://www.clward.com)

## Packaging

Item	Description	Packaging	Weight
SLS5	Super Liner Sealer 5 gallon pail	5 gallon pail	46 lbs/pail
SLS54	Super Liner Sealer 54 gallon drum	54 gallon drum	555 lbs/drum