

S-Seal Solvent

CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Detail

Premium grade solvent based duct sealant.



- UL Classified
- Permanently Flexible
- Fast Drying
- Will not drip or sag
- High water resistance
- For use in applications to 15" w.g.
- Low brush drag
- Excellent spreadability
- Minimal shrinkage
- Excellent adhesion to metal
- Indoor or outdoor use
- Superior sealing strength
- Conforms of requirements of NFPA 90A and 90B
- Mildew resistant
- U.S.D.A. chemically acceptable
- Base: Synthetic rubber
- Color: Grey
- Type: Solvent Base
- Weight: 9 lbs per gallon
- Solid Contents: 51%
- Viscosity: 150,000 cps
- Application Temperature: 0°F to 110°F
- Cure Temperature: 40°F to 110°F
- Service Temperature: -20°F to 190°F
- Storing Conditions: Room temperature (w/cross ventilaiton)
- Dry to Touch: 15 minutes
- Cure Time: 24 to 72 hours (depending on humidity,application and temperature)
- Flammability: (wet) Extremely Flammable, Flash Point -4°F
- Mildew Resistance: Excellent
- Water Resistance: Excellent
- Coverage: 25 sq.ft./gallon at 1/16" - 12.5 sq.ft./gallon at 1/8"
- Odor: Mild solvent (wet) None (dry)
- Shelf Life: 1 year (unopened container)
- Cured State: Tough and permanently flexible
- DOT Shipping Information: Flammable Liquid, N.O.S., 3, UN 1993, PG III. (Hexane CAS 110-54-3)
- Flame Spread - 5 Smoke Developed - 0



Packaging

Item	Description	Packaging	Weight
WSS11	S-Seal Solvent 11oz Tube	24 tubes/case	25 lbs/case
WSS1	S-Seal Solvent 1 gal	4 gallon/case	36 lbs/case