

# DuctGuard™

## CONTACT

Office: 888.973.7600

1100 Ashwood Drive  
Suite 1102  
Canonsburg, PA 15317

[www.clward.com](http://www.clward.com)


## Detail

- Film Thickness: 2.0 mil and 3.0 mil (HP)
- High tack adhesive
- Will not leave residue on duct
- UV Resistant film
- Material: Polyethylene self adhesive film
- Color: Clear or Blue
- Hazardous Components: NONE
- Soluble in Water: NONE
- PH: NONE
- Melting Temperature: 190°F
- Flash Point: 350°F
- Ignition Temperature: 370°
- Explosion Limits: NONE
- Thermal Decomposition: When you heat to 210°F, gaseous decomposition product that is a harmless irritant will be released.
- Environmental Hazard: Owing to the product's consistence, dispersion in environment is not possible. Waste can be recycled.
- Dangerous Material: The product is not subject to "Dangerous Material Regulation".



## Profile

- 24" x 200' roll
- 36" x 200' roll
- 48" x 200' roll



## Packaging

Item Code	Description	Packaging
DG24	24" DuctGuard - Clear	1/box - 48/pallet
DG24B	24" DuctGuard - Blue	1/box - 48/pallet
DG36	36" DuctGuard - Clear	1/box - 36/pallet
DG36B	36" DuctGuard - Blue	1/box - 36/pallet
DG48	48" DuctGuard - Clear	1/box - 36/pallet
DG48B	48" DuctGuard - Blue	1/box - 36/pallet
DG24HP	24" DuctGuard - Clear High Puncture	1/box - 48/pallet
DG36HP	36" DuctGuard - Clear High Puncture	1/box - 36/pallet
DG24BHP	24" DuctGuard - Blue High Puncture	1/box - 48/pallet
DG36BHP	36" DuctGuard - Blue High Puncture	1/box - 36/pallet