

TEE Gasket

CONTACT


Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Detail

Industrial grade butyl sealing tape for TDC and TDF Connections and other rectangular duct connections.



- Solids: 99.8%
- Color: Grey
- Hardness: 77°F - 9.0mm - 10.5mm max
- Shelf Life: 1 year minimum
- Life Expectancy: 20 years minimum
- Plasticizer Migration: No bleed/contact stain
- Staining: No bleed/contact skin
- Elongation & Webbing: 0°F 250% min., 77°F 800% min.
- Service Temperature: -40°F to 190°F
- Flexibility: Passes, no cracking or loss of adhesion
- Water Resistance: Vacuum .75% max, Static 0%
- Adhesion: Excellent to most non-porous surfaces
- Tested to the equivalent of UL 723/ASTM E 84
- Flame Spread: 10
- Smoke Developed: 10
- No VOC's
- CDPH Compliant
- U.S.D.A. Acceptability: Product chemically acceptable to the U.S. Department of Agriculture for use in meat and poultry processing areas under Federal inspection.
- F.D.A. Requirements: Meets Requirement 21CFR175.105

Profile

- 3/16" x 5/8"

Packaging

Item Code	Item Description	Packaging	Weight
TEE GASKET	TEE GASKET Butyl Gasket	500 ft/case (25 ft rolls)	40 lbs/box