

WB - Butyl Sealant

Detail

"Pumpable" non-drying sealant for the sealing of Pittsburgh seams. Works well this coil lines and stand alone pumping systems.

- Solids: 90%
- Color: Off White
- LEED Compliant
- CDPH Compliant
- FDA Approved
- Density: 1.45 gm/cc+ .05
- Weight per Gallon: 12.3 pounds Pounds ±.3
- Flash Point: 128°F-Penske Martens CC (ASTM E-134)
- Life Expectancy: 20 years minimum
- Service Temperature: -65°F to +200°F
- Oil Migration: None (applied to galvanized steel and subjected to a temperature of 158° for one week)
- Flexibility: No cracks when bent around a 1/4" mandrel after being subjected to 3 weeks at 75°F, 24 weeks at -40°F and 3 weeks at 158°F
- Adhesion: Excellent to most non-porous surfaces
- Application Consistency: Hand or power pump equipment
- Specifications: AAMA 802.2; NAAMSS-1a-68
- Flame Spread: 5
- Fuel Contribution: 0
- Smoke Density: 0
- Non-skinning
- Nonoxidizing
- Non-drying



CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Packaging

Item	Description	Packaging	Weight
WBT	CL WARD Butyl Sealant - 10.1 oz Tubes	12 tubes/case	7 lbs/case
WB5	CL WARD Butyl Sealant - 5 gal pail	Each	65 lbs/pail
WB55	CL WARD Butyl Sealant - 55 gal drum	Each	625 lbs/drum