

Duct Liner Adhesive - HV

Qualifies for LEED Credit EQ 4.1

Detail

Premium grade high viscosity duct liner adhesive.

- Water Based
- UL Classified
- Fast Dry Time
- Coverage: 400 sq.ft./gal.
- Apply by Brush, Spray or Roto Bond
- Water Resistant
- Cleans with soap and water or mineral spirits
- Excellent Tack
- Base: Premium Latex
- Color: Black
- Solvent: Water
- Weight per Gallon: 9.0 ± 0.5 lbs.
- Solids: 64 ± 2%
- Viscosity: 9,000 CP ± 2,000 CP
- Application Temp: 20°F to 90°F
- Storage Temp: 20°F to 90°F
- Dry Time: 8 minutes, depending on temperature, humidity, and application thickness
- Flammability: None
- Flash Point: No flash to boiling
- Freeze Thaw Stability: 5 cycles
- Shelf Life: (Unopened containers) 1 year
- Flame Spread: 0
- Smoke Developed: 0
- Meets ASTM C 916 Type II
- Meets NFPA 90A & 90B
- LEED v4 Compliant
- VOC Content: 20.3 g/L
- Contains antimicrobials and fungicides to prevent mold growth
- Meets CDPH and EPA Method 24



CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Packaging

Item	Description	Packaging	Weight
DLADHESIVEHV5B	High Viscosity D L Adhesive - Black 5 gal pail	Each	46 lbs/pail
DLADHESIVEHV54B	High Viscosity D L Adhesive - Black 54 gal drum	Each	555 lbs/drum
DLADHESIVEHV5W	High Viscosity D L Adhesive - White 5 gal pail	Each	46 lbs/pail
DLADHESIVEHV54W	High Viscosity D L Adhesive - White 54 gal drum	Each	555 lbs/drum