

# Duct Liner Adhesive

Qualifies for LEED Credit EQ 4.1

## Detail

Premium grade duct liner adhesive.

- Water Based
- UL Classified
- Fast Dry Time
- Exceptional Coverage: 400 sq.ft./gal
- Apply by Brush, Spray or Roto Bond
- Water Resistant
- Cleans with soap and water or mineral spirits
- Excellent Tack
- Color: Black or White
- Solvent: Water
- Weight per Gallon: 8.1 ± 0.5 lbs.
- Solids: 46 ± 2%
- Viscosity: 4,000 cPs ± 2,000 cPs
- Application Temp: 20°F to 90°F
- Storage Temp: 20°F to 90°F
- Dry Time: 15 minutes at 76°F, depending on temperature, humidity, and application thickness
- Flammability: None
- Flash Point: No flash to boiling
- Freeze Thaw Stability: 5 cycles
- Shelf Life: (Unopened containers) 1 year
- Flame Spread: 0
- Smoke Developed: 0
- Meets ASTM C 916 Type II
- Meets NFPA 90A & 90B
- LEED 4v Compliant
- Meets CDPH and EPA Method 24
- VOC Content: 20.3 g/L
- Contains antimicrobials and fungicides to prevent mold growth



## CONTACT

Office: 888.973.7600

1100 Ashwood Drive  
Suite 1102  
Canonsburg, PA 15317

[www.clward.com](http://www.clward.com)

## Packaging

Item	Description	Packaging	Weight
DLADHESIVE5B	Duct Liner Adhesive - Black 5 gal pail	Each	46 lbs/pail
DLADHESIVE54B	Duct Liner Adhesive - Black 54 gal drum	Each	555 lbs/drum
DLADHESIVE5W	Duct Liner Adhesive - White 5 gal pail	Each	46 lbs/pail
DLADHESIVE54W	Duct Liner Adhesive - White 54 gal drum	Each	555 lbs/drum