

EcoSeal

LEED Compliant, Meets All Applicable SCAQMD Standards

Detail

Industrial grade water based duct sealant.

- Indoor and outdoor use
- UL 723 Classification
- UL 181B-M Listed
- Manufactured by SMART Local #12
- Non-Flammable
- Water Based
- Base: Engineered Polymer emulsion
- Recommended up to 10" wg
- Color: Gray
- Type: Water Base
- Paintable: Latex or Epoxy Paints
- Weight: 11.3±.2 lbs per gallon
- Solid Contents: 66% ±3%
- Viscosity: 320,000 c.p.s.
- VOC Content: ASTM3690-05(13) - 1.3 g/L
- Application Temp: 35°F to 110°F
- Service Temp: 0°F to 220°F
- Storage Temp: 35°F to 110°F
- Dry To Touch: 1 hour (approx.)
- Cure Time: 24 to 72 hours + (depending on humidity, application, and temperature)
- Flammability: Non-flammable in both wet and dry state
- Flash Point: No flash to boiling
- Mold Resistance: UL 181B Mold & Humidity Test - Pass
- Water Resistance: Excellent
- Flexibility: Excellent
- Freeze Thaw Stability: 5 cycles
- Odor: Mild (wet) None (dry)
- Shelf Life: 1 year (unopened container)
- Cured Sealant: Tough and permanently flexible
- UV Resistant
- LEED Compliant, meets all applicable SCAQMD standards

* Total VOC's after 14 days is between .5 and 5.0 mg/m³ measured as specified in the CDPH Standard Method v1.1



Caulking and Sealants
Control No.
SURFACE BUILDING CHARACTERISTICS
EcoSeal

USC - Classification
Applied to Inorganic Reinforced Cement Board
FHC 25/50
+ - Tested as applied in two 2 in. wide strips spaced 8 in. on center (covering 22.2% of the exposed test sample area) at a coverage rate of 25 ft²/gallon

CNC - Classification
Applied to Inorganic Reinforced Cement Board
FHC 25/50
+ - Tested as applied in two 50mm wide strips spaced 200mm on center (covering 22% of the exposed test sample area) at a coverage rate of .61 to .73 m²/L²

The FHC 25/50 "Fire Hazard Classification" indicates that the labeled material has a flame spread of 25 or less and a smoke developed of 50 or less as tested per UL723 or equivalent.

CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Packaging

Item	Description	Packaging	Weight
ECOSEALT	EcoSeal 11oz Tube	25 tubes/case	25 lbs/case
ECOSEAL1	EcoSeal 1 gal	4 gallon/case	50 lbs/case
ECOSEAL5	EcoSeal 5 gal	Each	64 lbs/pail
ECOSEAL54	EcoSeal 54 gal	Each	700 lbs/drum

