

# Lag Adhesive

Qualifies for LEED Credit EQ 4.1

## Detail

Lagging adhesive is used for bonding and sealing jackets of canvas, cloth or other fabrics and insulators to air conditioning ducts or cold water pipes.

- Water Based
- ASTM E-84 Certified
- Low odor
- Fire retardant in dry state
- UV resistant
- Sag resistant
- Can be applied via spray or brush
- Great flexibility
- Base: Acrylic Latex
- Color: White or Black
- Weight/Gal: 11.3 lbs ±.3
- Viscosity: app. 80,000 cp +/- 20,000 cp
- Application Temp: 35°F to +110°F
- Storage Temp: 35°F to +110°F
- Flammability: None
- Flash Point: No flash
- Dry Time: 1 hour
- Freeze Thaw: 5 cycles
- Coverage: 200 sq.ft./gal
- Bonding Time: 40 minutes
- Shelf Life: 1 Year (unopened)
- LEED Compliant—Meets CDPH and EPA Method 24
- VOC Content: 1.3 g/L



## CONTACT

Office: 888.973.7600

1100 Ashwood Drive  
Suite 1102  
Canonsburg, PA 15317

[www.clward.com](http://www.clward.com)

## Packaging

Item	Description	Packaging	Weight
LAGADHESIVE1B	Lagging Adhesive 1 gal Black	4 gallons/case	48 lbs/case
LAGADHESIVE1W	Lagging Adhesive 5 gal pail White	Each	64 lbs/pail
LAGADHESIVE5B	Lagging Adhesive 1 gal Black	4 gallons/case	48 lbs/case
LAGADHESIVE5W	Lagging Adhesive 5 gal pail White	Each	64 lbs/pail