

S-Seal Solvent - LOW VOC

Detail

Premium grade low VOC solvent based duct sealant that is LEED compliant/CDPH.

- Low VOC's
- Permanently Flexible
- Fast Drying
- Will not drip or sag (Sag/Slump - Pass, ASTM D522)
- High water resistance
- For use in applications to 15" w.g.
- Low brush drag
- Excellent spreadability
- Minimal shrinkage
- Excellent adhesion to metal
- For indoor use only
- Superior sealing strength
- Conforms to requirements of NFPA 90A and 90B
- Mildew resistant
- U.S.D.A. chemically acceptable
- Base: Synthetic rubber
- Color: Grey
- Type: Solvent Base
- Weight: 9 lbs per gallon
- VOC Content: 193 g/L (EPA Method 24)
- TVOC Emissions: Private Office - Pass, School Classroom - Pass (CDPH Standard Method v1.1)
- Solid Contents: 67%
- Viscosity: 152,300 cps
- Application Temperature: 0°F to 110°F
- Cure Temperature: 40°F to 110°F
- Service Temperature: -20°F to 190°F
- Storage Temperature: 35°F to 110°F
- Dry to Touch: 15 minutes
- Cure Time: 24 to 48 hours (depending on humidity,application and temperature)
- Flammability: (wet) Extremely Flammable, Flash Point -4°F
- Freeze Thaw Stability: Pass
- Coverage: Approximately 50 to 75 sq. ft. per gallon
- Coverage: 25 sq.ft./gallon at 1/16" - 12.5 sq.ft./gallon at 1/8"
- Odor: Mild solvent (wet) None (dry)
- Shelf Life: 1 year (unopened container)
- Flame Spread - 5 Smoke Developed - 0 (ASTM E84)



CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317
Can

www.clward.com

Packaging

Item	Description	Packaging	Weight
WSS11LVOC	S-Seal Solvent 11oz Tube	24 tubes/case	25 lbs/case
WSS1LVOC	S-Seal Solvent 1 gal	4 gallon/case	36 lbs/case

