

SuperSpray

Qualifies for LEED Credit EQ 4.1

Detail

A nonflammable duct liner adhesive that provides a strong hold with quick dry time. SuperSpray is suitable for all types of HVAC insulations such as elastomeric, fiberglass, polyester and even substrates like plywood.

- Color: Light Yellow to Clear
- Spray Pattern: Web
- Tack: Extremely Aggressive Wet Tack, Permanent dry tack
- Flammability: Non-flammable
- Propellant: Methylene Chloride
- Coverage: \geq 4,000 sq.ft per Canister
- VOC's: 0 g/L
- Low odor
- Solid Content: 29-35%
- Application Temperature: 60-100°F
- Maximum Storage Temperature: 120°F
- Dry Time: 2-4 minutes
- 7L and 22L are disposable/recyclable containers
- 108L and 216L are custom ordered and returnable containers
- Shelf Life: 18 months
- Less weight per canister than competing brands



Coverage Rate - Single pass application with 80 to 100% coverage.

Packaging

Item	Description	Packaging	Weight
SUPERSPRAY7	SuperSpray 7L Canister	Each	8 lbs
SUPERSPRAY22	SuperSpray 22L Canister	Each	33 lbs
SUPERSPRAY108	SuperSpray 108L Canister	Each	152 lbs
SUPERSPRAY216	SuperSpray 216L Canister	Each	303 lbs
SSH6	SuperSpray Hose 6 ft	Each	2 lbs
SSH8	SuperSpray Hose 8 ft	Each	5 lbs
SSH12	SuperSpray Hose 12 ft	Each	4 lbs
SSH18	SuperSpray Hose 18 ft	Each	6 lbs
SSG	SuperSpray Gun	Each	4 lbs

CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317
Can

www.clward.com