

SuperSpray-NM

LEED Compliant

Detail

A **methylene chloride free** duct liner adhesive that provides a strong hold with quick dry time. SuperSprayNM is suitable for all types of HVAC insulations such as elastomeric, fiberglass, polyester and even substrates like plywood.

- Color: Light Yellow to Clear
- Spray Pattern: Web
- Tack: Extremely Aggressive Wet Tack, Permanent dry tack
- Flammability: Flammable (in wet state only)
- Propellant: Methyl Acetate
- Coverage: $\geq 4,000$ sq.ft per Canister
- California SCAQMD 1168 Rule Compliant
- HAPS Free (Hazardous Air Pollutants)
- VOC's: 43 g/L
- Low odor
- Solid Content: 30-38%
- Application Temperature: 60-100°F
- Maximum Storage Temperature: 120°F
- Dry Time: 2-4 minutes
- 7L and 22L are disposable/recyclable containers
- 108L and 216L are custom ordered and returnable containers
- Shelf Life: 18 months
- Less weight per canister than competing brands



Coverage Rate - Single pass application with 80 to 100% coverage.

Packaging

Item	Description	Packaging	Weight
SUPERSPRAYNM7	SuperSpray, No Methylene Chloride, 7L Canister	Each	8 lbs
SUPERSPRAYNM22	SuperSpray, No Methylene Chloride, 22L Canister	Each	33 lbs
SUPERSPRAYNM108	SuperSpray, No Methylene Chloride, 108L Canister	Each	152 lbs
SUPERSPRAYNM216	SuperSpray, No Methylene Chloride, 216L Canister	Each	303 lbs
SSH8	SuperSpray Hose 8 ft	Each	5 lbs
SSH12	SuperSpray Hose 12 ft	Each	4 lbs
SSH18	SuperSpray Hose 18 ft	Each	6 lbs
SSG	SuperSpray Gun	Each	4 lbs

CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317
Can

www.clward.com