

SuperSpray

Qualifies for LEED Credit EQ 4.1

Detail

Premium quality, pressure sensitive adhesive for a quick permanent tack. A great product for bonding insulation or other materials to smooth nonporous surfaces.

- Pressure sensitive
- Methylene chloride based
- Non-flammable
- Solvent base
- Green in color
- Service Temperature: -30° to 160°F
- Application Temperature: 60° to 90°F
- Storage Temperature: Below 120° F
- Flammability: None
- Flashpoint: None
- Freeze thaw: Does not apply
- Coverage: 12 lb - 1,200 sq.ft. to 1,385 sq.ft.
40 lb - 4,000 sq.ft. to 4,600 sq.ft.
- Bonding time: 1 to 10 minutes (Depending on applicatoion rate)
- Shelf life: 1 year
- High solids content (25%)
- Easy application
- Exptremely quick tack
- Strong permanent bond
- Meets DOT 39 NRC
- Non-Flammable in wet and dry state
- Ultraviolet Ray and Ozone resistant
- LEED Compliant



CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Packaging

Item	Description	Packaging	Weight
SUPERSPRAY12	SuperSpray 12# Canister	Each	12 lbs
SUPERSPRAY40	SuperSpray 40# Canister	Each	40 lbs
SSH6	SuperSpray Hose 6 ft	Each	2 lbs
SSH8	SuperSpray Hose 8 ft	Each	5 lbs
SSH12	SuperSpray Hose 12 ft	Each	4 lbs
SSH18	SuperSpray Hose 18 ft	Each	6 lbs
SSG	SuperSpray Gun	Each	4 lbs